



YOMANI TOUCH XR

The intuitive terminal with touch function

Elegant design and a clear user interface make the YOMANI Touch XR
the perfect solution for the highest demands.

Thanks to its fast data processing, clear user interface and elegant design, the YOMANI Touch XR is the ideal terminal for payments at all points of sale.

The touch screen and the integrated NFC reader on the side of the terminal contribute to the positive customer experience.

YOUR ADVANTAGES AT A GLANCE

The YOMANI Touch XR ensures maximum flexibility for your business:

- Touch screen for enhanced user-friendliness
- Contactless function to make payments even quicker
- Full card acceptance for increased customer satisfaction
- Additional value-added solutions available, such as Dynamic Currency Conversion (DCC)



Technical specifications

Product versions

YOMANI TOUCH XR PINPAD

Terminal for integrated operation



YOMANI TOUCH XR AUTONOM

Combination of Pinpad and merchant unit for autonomous operation



YOMANI TOUCH XR COMPACT

Pinpad terminal with printer for integrated operation



Technical details

	YOMANI TOUCH XR PINPAD	MERCHANT UNIT FOR YOMANI TOUCH XR AUTONOM	YOMANI TOUCH XR COMPACT
Dimensions (l x w x h)	170 × 116 × 105 mm	228 × 91 × 68 mm	230 × 116 × 105 mm
Weight	650 g	309 g	800 g
Communication	LAN	USB connection between the terminal unit and merchant unit Optional Wifi/3G	LAN Optional Wifi/3G
Power supply	External power unit	External power unit	External power unit
Display (pixels)	Colour display 320 × 240	LCD display 128 × 64	Colour display 320 × 240
Screen size	3,5"	3,2"	3,5"
Thermal printer	–	Yes – receipt printing from the merchant unit	Yes – receipt printing from the terminal
Security certificate	PCI PTS 5.x	–	PCI PTS 5.x
Point of sale integration	TIM	–	TIM
Card reader	EMV chip Magnetic strip Contactless	–	EMV chip Magnetic strip Contactless
Ambient conditions	Operating temperature: 0 °C to 50 °C Storage temperature: –10 °C to 60 °C Relative humidity: 5% to 90% No thawing	Operating temperature: 0 °C to 50 °C Storage temperature: –10 °C to 60 °C Relative humidity: 5% to 90% No thawing	Operating temperature: 0 °C to 50 °C Storage temperature: –10 °C to 60 °C Relative humidity: 5% to 90% No thawing
Options	Fixing panel Assembly stand	–	Fixing panel Rotary plate Assembly stand

Your local point of contact can be found at: worldline.com/merchant-services/contacts

